## NSN 4730-01-243-5818

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-243-5818 **Thread Class:** 3a first fluid end connection Second End Style Designator (non-core): Err-090 Second Leg Length: 0.840 inches **Quick Disconnect Method:** Spring push-lock all ends **Second Fluid End Connection Type:** Threaded external tube **Connection Style:** Flared first fluid end connection Leg Length: 1.018 inches **Connection Type:** Threaded external tube first fluid end connection Second End Relationship With First End: Not identical Maximum Operating Pressure And Media For Which Designed: 4500.0 pounds per square inch any acceptable **Maximum Operating Pressure:** 4500.0 pounds per square inch single response Thread Size: 0.4375 inches first fluid end connection Seat Angle: 37.0 degrees **Outside Diameter Tube Accommodated:** 0.250 inches first fluid end connection **Special Features:** U/o gbu-10, 12, 24 Material: Stainless steel **Material Specification:** Ams5643 assn standard single material response **Style Designator:** Coupling assembly **Thread Series Designator:** Unjf first fluid end connection Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 4730-01-243-5818

Quick Disconnect Coupling Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A531s0