## NSN 4730-01-248-3866

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-248-3866 **Thread Class:** 3a first fluid end connection **Quick Disconnect Method:** Twist-lock all ends **Maximum Operating Temp:** 71.0 degrees celsius single response **Connection Style:** Flared first fluid end connection **Connection Type:** Threaded external tube first fluid end connection **Features Provided:** Self-sealing Thready Qty Per Inch (tpi): 12 first fluid end connection Second End Relationship With First End: Identical **Maximum Operating Pressure And Media For Which Designed:** 600.0 pounds per square inch any acceptable **Maximum Operating Pressure:** 600.0 pounds per square inch single response **Thread Size:** 1.875 inches first fluid end connection Seat Angle: 37.0 degrees Maximum Operating Tempurature And Media For Which Designed: 71.0 degrees celsius any acceptable **Outside Diameter Tube Accommodated:** 1.500 inches first fluid end connection Material: Aluminum alloy **Surface Treatment:** Anodize **Style Designator:** Coupling assembly **Thread Series Designator:** Un first fluid end connection Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 4730-01-248-3866

Quick Disconnect Coupling Assembly - Page 2 of 2



Fiig:

A531s0