NSN 4730-01-260-8003

Tube To Hose Elbow - Page 1 of 2



| _ | |
|---|--|
| | View Online at https://aerobasegroup.com/nsn/4730-01-260-8003 |
| | Thread Class: |
| | 3b 1st end |
| | Maximum Operating Temp: |
| | 400.0 degrees fahrenheit single response |
| | Connection Style: |
| | Swivel nut, flare (tube) style 3 optional end 1st end |
| | Leg Length: |
| | 0.500 inches 1st end |
| | Connection Type: |
| | Unthreaded external hose 2nd end |
| | Maximum Operating Pressure: |
| | 3000.0 pounds per square inch single response |
| | Thread Size: |
| | 0.438 inches 1st end |
| | Seat Angle: |
| | 37.0 degrees 1st end |
| | Flow Angle: |
| | 45.0 degrees |
| | Inside Diameter Hose Accommodated: |
| | 0.212 inches 2nd end |
| | Outside Diameter Tube Accommodated: |
| | 0.390 inches 1st end |
| | Material: |
| | Steel comp 304 |
| | Material Specification: |
| | Qq-s-763, uns s30400 federal specification single material response |
| | Media For Which Designed: |
| | Fluid single response |
| | Surface Treatment: |
| | Passivate |
| | Surface Treatment Specification: |
| | As1339 assn standard single treatment response |
| | Thread Series Designator: |
| | Unjf 1st end |
| | Furnished Items And Quantity: |
| | 1 swivel nut |
| | Fsc Application Data: |
| | Mfr eng bulletin aeb209a cprs crimp fitting u/o ae246 hose; as1339, as154-04 and a 156e and as157e |
| | Shelf Life: |
| | N/a |
| | |

Unit Of Measure:

--

NSN 4730-01-260-8003

Tube To Hose Elbow - Page 2 of 2



Demilitarization:

No

Fiig:

A080b0