NSN 4730-01-261-6601

Sediment Strainer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-261-6601

Mounting Type:
Unthreaded hole line
Mounting Hole Diameter:
0.688 inches
Mounting Hole Quantity:
8
Body Length:
15.125 inches
Distance Between Mounting Hole Centers:
0.820 inches
Perforation Diameter:
0.057 inches
Perforation Quantity:
144.0 per square inch
Tempurature Rating:
150.0 degrees fahrenheit
Maximum Operating Pressure:
500.0 pounds per square inch
Filtering Media Design:
Perforated single filtering media response
First Intake Connection Type:
Plain face flange line
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
Distance From Bottom Of Body To Center Of Inlet:
10.875 inches
First Intake Flange Outside Diameter:
7.688 inches
First Intake Flange Shape Style:
Round w/unthreaded bolt holes
First Intake Flange Face Style:
Plain
First Intake Flange Thickness:
1.000 inches
Material:
Nickel alloy screening
Material Specification:
B-61 assn standard 1st material response body
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:

Y strainer w/blow-off plug

NSN 4730-01-261-6601

Sediment Strainer - Page 2 of 2



Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources;	76588 have indicated their part number contained
asbestos prior to 1984, they continue to manufacture the same part number withou	ut asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000