NSN 4730-01-287-3110

Tube Fitting Locknut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-287-3110

| Thread Class. |
|---|
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Fabrication Method: |
| Machined |
| Nut Style: |
| Tube fitting locknut |
| Nut Height: |
| 0.535 inches |
| Drilled Hole Diameter: |
| 0.046 inches |
| Hole Type And Quantity: |
| 3 drilled |
| Width Across Flats: |
| 1.688 inches |
| Thread Series: |
| Unj |
| Packing Recess Diameter: |
| 1.477 inches |
| Packing Recess Depth: |
| 0.151 inches |
| Thready Qty Per Inch (tpi): |
| 12 |
| Thread Size: |
| 1.312 inches |
| Tube Outside Diameter: |
| 1.000 inches |
| Hole Configuration Style: |
| Configuration b |
| Special Features: |
| Furnished with three number 56 diameter 0.046 lockwire holes at 120degree |
| Material: |
| Steel comp 304 |
| Material Specification: |
| Qq-s-763 federal specification single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Specification Data: |

80205-nas1410 professional/industrial association standard

NSN 4730-01-287-3110

Tube Fitting Locknut - Page 2 of 2



| _ | | | | | |
|---|-----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | 116 | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0