4

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4730-01-302-2044 Thread Class: 2a 1st end Connection Style: Plain (pipe) 2nd end Leg Length: 1.469 inches 2nd end Connection Type: 1.469 inches 2nd end Connection Type: Threaded external tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response boot
2a 1st end Connection Style: Plain (pipe) 2nd end Leg Length: 1.469 inches 2nd end Connection Type: Threaded external tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Connection Style: Plain (pipe) 2nd end Leg Length: 1.469 inches 2nd end Connection Type: Threaded external tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Plain (pipe) 2nd end Leg Length: 1.469 inches 2nd end Connection Type: Threaded external tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.562 inches 1st end Seat Angle: 0.562 inches 1st end Seat Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qa-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Leg Length: 1.469 inches 2nd end Connection Type: Threaded external tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
 1.469 inches 2nd end Connection Type: Threaded external tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Connection Type: Threaded external tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Threaded external tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Maximum Operating Pressure:3000.0 pounds per square inch single responseThread Size:0.562 inches 1st endSeat Angle:37.0 degrees 1st endFlow Angle:90.0 degreesOutside Diameter Tube Accommodated:0.375 inches 1st endMaterial:Steel comp 316 or steel comp 304Material Specification:Fedstd 66, comp 300 series federal standard single material responseMedia For Which Designed:Hydraulic fluid single responseSurface Treatment:Passivate bodySurface Treatment Specification:Qa-p-35, type 2, cl 3 federal specification single treatment response body
3000.0 pounds per square inch single response Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body
Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body
 37.0 degrees 1st end Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
0.375 inches 1st end Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Material: Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Steel comp 316 or steel comp 304 Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Material Specification: Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Fedstd 66, comp 300 series federal standard single material response Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Hydraulic fluid single response Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Surface Treatment: Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Passivate body Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Surface Treatment Specification: Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Qq-p-35, type 2, cl 3 federal specification single treatment response body Thread Series Designator:
Thread Series Designator:
-
Unf 1st end
Specification Data:
96906-ms51504 government standard
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:

Fiig:

A080b0