NSN 4730-01-319-5932

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-319-5932

Thread Class: 3a first fluid end connection **Overall Length:** 2.570 inches Second Leg Length: 0.550 inches **Quick Disconnect Method:** Twist-lock all ends **Maximum Operating Temp:** 65.0 degrees fahrenheit single response **Connection Style:** Flared first fluid end connection Leg Length: 1.047 inches **Connection Type:** Threaded external tube first fluid end connection Second End Relationship With First End: Identical Maximum Operating Pressure And Media For Which Designed: 3000.0 pounds per square inch hydraulic fluid, petroleum base **Maximum Operating Pressure:** 3000.0 pounds per square inch single response Thread Size: 0.438 inches first fluid end connection Seat Angle: 37.0 degrees **Maximum Operating Tempurature And Media For Which Designed:** Err-070 **Outside Diameter Tube Accommodated:** 0.750 inches first fluid end connection **Special Features:** First end bulkhead threads-1/4inch unif-7/16-20 3a; 1817 series ball bearing plane swivel joints to provide a flexible joint in rigid lines to prevent binding or twisting Material: Stainless steel **Special Test Features:** Are qualified to mil-j-5513rev.C **Style Designator:**

Shelf Life:

Coupling assembly

Thread Series Designator: Unif first fluid end connection

N/a

NSN 4730-01-319-5932

Quick Disconnect Coupling Assembly - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A531s0