

View Online at <https://aerobasegroup.com/nsn/4730-01-383-5695>

Body Style:

Shoulder

Concentric Hole Depth:

Between 0.107 inches and 0.114 inches

Concentric Hole Diameter:

Between 0.107 inches and 0.114 inches

Overall Length:

Between 1.800 inches and 1.845 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Second End Connection Type:

Threaded internal tube

Second End Style Designator:

Double compression

Second End Thread Class:

3b

Second End Thread Direction:

Right-hand

Second End Seat Radius:

0.015 inches

End Application:

C-17a aircraft

Width Across Flats:

Between 0.553 inches and 0.564 inches

First End Thread Length:

Between 0.417 inches and 0.422 inches

Second End Thread Length:

0.250 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

Between 0.339 inches and 0.369 inches

Second Diameter From Wrenching Feature:

Between 0.249 inches and 0.259 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

Between 1.082 inches and 1.092 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

Between 1.195 inches and 1.220 inches

First Radial Fluid Hole Diameter:

Between 0.107 inches and 0.114 inches

Distance From First Radial Hole Center To End Of Bolt:

Between 0.805 inches and 0.825 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

Between 1.612 inches and 1.642 inches

Wrenching Feature Height:

Between 0.188 inches and 0.203 inches

First End Thread Series Designator:

Unjc

First End Thread Size:

0.312 inches

Second End Thread Size:

0.250 inches

Second End Thread Series Designator:

Unf

Special Features:

Furnished with a lubrication fitting located on the second end

Material:

Nickel alloy

Surface Treatment:

Chromate

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0