## NSN 4730-01-383-5867

Fluid Passage Bolt - Page 1 of 2

**Body Style:** Shoulder



View Online at https://aerobasegroup.com/nsn/4730-01-383-5867

Concentric Hole Depth:
Between 1.464 inches and 1.474 inches
Concentric Hole Diameter:
Between 0.107 inches and 0.114 inches
Overall Length:
Between 3.179 inches and 3.224 inches
First End Connection Type:
Threaded external tube
First End Style Designator:
Plain
First End Thread Class:
3a
First End Thread Direction:
Right-hand
Second End Connection Type:
Threaded internal tube
Second End Style Designator:
Double compression
Second End Thread Class:
3b
Second End Thread Direction:
Right-hand
Second End Seat Radius:
0.015 inches
End Application:
C-17a aircraft
Width Across Flats:
Between 1.052 inches and 1.064 inches
First End Thread Length:
Between 0.646 inches and 0.650 inches
Second End Thread Length:
0.250 inches
Wrenching Feature Style:
Hexagon
First Diameter From Wrenching Feature:
Between 1.212 inches and 1.242 inches
Second Diameter From Wrenching Feature:
Between 0.426 inches and 0.436 inches
Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:
Between 2.022 inches and 2.032 inches

## NSN 4730-01-383-5867

Fluid Passage Bolt - Page 2 of 2

A121a0



Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:	
Between 2.258 inches and 2.283 inches	
First Radial Fluid Hole Diameter:	
Between 0.107 inches and 0.114 inches	
Distance From First Radial Hole Center To End Of Bolt:	
Between 1.340 inches and 1.360 inches	
Length From Bearing Surface Of Wrenching Feature To Bolt End:	
Between 2.804 inches and 2.834 inches	
Wrenching Feature Height:	
Between 0.375 inches and 0.390 inches	
First End Thread Series Designator:	
Unjc	
First End Thread Size:	
0.500 inches	
Second End Thread Size:	
0.250 inches	
Second End Thread Series Designator:	
Unf	
Special Features:	
Furnished with a lubrication fitting located on second end	
Material:	
Nickel alloy	
Surface Treatment:	
Cadmium	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	