## NSN 4730-01-395-3463

Sediment Strainer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-395-3463

**Mounting Type:** 

Inlet connection line and outlet connection line

**Body Length:** 

8.438 inches

**End Application:** 

Ships; 170 ft patrol coastal (pc-1) class

**Perforation Diameter:** 

0.045 inches

**Perforation Quantity:** 

225.0 per square inch

**Tempurature Rating:** 

Between 150.0 degrees fahrenheit and 405.0 degrees fahrenheit

**Maximum Operating Pressure:** 

225.0 pounds per square inch

Filtering Media Design:

Perforated single filtering media response

**First Intake Connection Type:** 

Plain face flange line

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

**Distance From Bottom Of Body To Center Of Inlet:** 

6.000 inches

First Intake Flange Outside Diameter:

6.000 inches

First Intake Flange Shape Style:

Round w/unthreaded bolt holes

First Intake Flange Face Style:

Plain

First Intake Flange Thickness:

0.750 inches

**Special Features:** 

Gasket; non-asbestos; plug not furnished; working pressure; steam 150 psi, wog 225 psi; temp rating; steam 405 degrees f, wog 150

degrees f; removal clearance - 8 1/2 inches required

Material:

Steel comp 316 filtering medium

**Material Specification:** 

Astm b62 assn standard single material response body

Media For Which Designed:

Fuel/oil, hydrocarbon and gas and water

**Style Designator:** 

Y strainer w/bolted cover

Shelf Life:

N/a

## NSN 4730-01-395-3463

Sediment Strainer - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A24000