

View Online at <https://aerobasegroup.com/nsn/4730-01-396-1309>

Mounting Type:

Unthreaded hole line

Mounting Hole Diameter:

0.625 inches

Mounting Hole Quantity:

4

Body Length:

7.000 inches

Distance Between Mounting Hole Centers:

0.500 inches

End Application:

Ships; whidbey island, class lsd

Perforation Diameter:

0.045 inches

Perforation Quantity:

225.0 per square inch

Tempurature Rating:

225.0 degrees fahrenheit

Maximum Operating Pressure:

500.0 pounds per square inch

Filtering Media Design:

Perforated single filtering media response

First Intake Connection Type:

Plain face flange line

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

4.750 inches

First Intake Flange Outside Diameter:

5.250 inches

First Intake Flange Shape Style:

Round w/unthreaded bolt holes

First Intake Flange Face Style:

Plain

First Intake Flange Thickness:

0.750 inches

Special Features:

Steam, 450 degrees f, 300 psi; water-oil-gas, 100 degrees f, 500 psi

Material:

Copper alloy body

Material Specification:

Astm b-62 assn standard single material response body

Media For Which Designed:

Fuel/oil, hydrocarbon and gas and water

Style Designator:

Y strainer w/blow-off plug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000