NSN 4730-01-416-6808

Tube To Boss Straight Adapter - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/4730-01-416-6808 |
|--|
| Thread Class: |
| 3a all ends |
| Connection Style: |
| Flareless (tube) 1st end |
| Connection Type: |
| Threaded external tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Maximum Operating Pressure: |
| 4000.0 pounds per square inch single response |
| Thread Size: |
| 1.625 inches 1st end |
| Seat Angle: |
| 12.0 degrees 1st end |
| Outside Diameter Tube Accommodated: |
| 1.250 inches 1st end |
| Nominallength: |
| 1.614 inches |
| Material: |
| Titanium alloy uns r54520 body |
| Material Specification: |
| Ams5731 assn standard single material response lock ring or ams5734 assn standard single material response lock ring |
| Surface Treatment: |
| Passivate lock ring |
| Surface Treatment Specification: |
| Qq-p-35, ty ii federal specification single treatment response lock ring |
| Thread Series Designator: |
| Unjef 2nd end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A080b0 |
| |