NSN 4730-01-421-5257

Sediment Strainer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-421-5257

ALCOHOL TO A CONTRACT OF THE C
Mounting Type:
Bracket w/drilled hole base
Mounting Hole Diameter:
0.875 inches
Mounting Hole Quantity:
2
Body Length:
29.500 inches
Body Width:
19.250 inches
Body Height:
29.938 inches
Distance Between Mounting Hole Centers:
4.250 inches
End Application:
Nimitz class cvn
Perforation Diameter:
0.078 inches
Tempurature Rating:
120.0 degrees fahrenheit
Bracket Quantity:
2
2 Maximum Operating Pressure:
Maximum Operating Pressure:
Maximum Operating Pressure: 250.0 pounds per square inch
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design:
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type:
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Plain face flange center
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type:
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Plain face flange center First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Plain face flange center First Discharge Connection Relationship To Intake Connection:
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Plain face flange center First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 15.875 inches
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Plain face flange center First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet:
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Plain face flange center First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 15.875 inches First Intake Flange Outside Diameter: 9.062 inches
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Plain face flange center First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 15.875 inches First Intake Flange Outside Diameter: 9.062 inches First Intake Flange Shape Style:
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Plain face flange center First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 15.875 inches First Intake Flange Outside Diameter: 9.062 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Plain face flange center First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 15.875 inches First Intake Flange Outside Diameter: 9.062 inches First Intake Flange Shape Style:
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Plain face flange center First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 15.875 inches First Intake Flange Outside Diameter: 9.062 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes First Intake Flange Face Style: Plain
Maximum Operating Pressure: 250.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Plain face flange center First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 15.875 inches First Intake Flange Outside Diameter: 9.062 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes First Intake Flange Face Style:

water iar.

Nickel alloy filtering medium

NSN 4730-01-421-5257

Sediment Strainer - Page 2 of 2



Material Specification:	
Qq-n-281 cl a federal specification single material response filtering media	um

Media For Which Designed:

Water

Style Designator:

Twin strainer w/bolted cover

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000