

View Online at <https://aerobasegroup.com/nsn/4730-01-424-4675>

**Body Style:**

Plain

**Concentric Hole Depth:**

3.859 inches

**Concentric Hole Diameter:**

0.160 inches

**Overall Length:**

7.984 inches

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Plain

**First End Thread Class:**

3a

**First End Thread Direction:**

Right-hand

**Second End Connection Type:**

Threaded internal tube

**Second End Style Designator:**

High pressure flare

**Second End Thread Class:**

3b

**Second End Thread Direction:**

Right-hand

**Cotter Pin Hole Diameter:**

Between 0.131 inches and 0.151 inches

**End Application:**

Aircraft, airlifter c-17a

**Width Across Flats:**

Between 1.052 inches and 1.065 inches

**First End Thread Length:**

0.790 inches

**Second End Thread Length:**

0.188 inches

**Wrenching Feature Style:**

Hexagon

**Distance From Bolt End To Hole Center:**

Between 0.172 inches and 0.192 inches

**First Diameter From Wrenching Feature:**

0.7499 inches

**Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:**

6.812 inches

**First Radial Fluid Hole Diameter:**

0.125 inches

**Distance From First Radial Hole Center To End Of Bolt:**

4.125 inches

**Length From Bearing Surface Of Wrenching Feature To Bolt End:**

7.602 inches

**Wrenching Feature Height:**

Between 0.375 inches and 0.390 inches

**First End Thread Series Designator:**

Unjf

**First End Thread Size:**

0.7500 inches

**Second End Thread Size:**

0.250 inches

**Second End Thread Series Designator:**

Unjf

**Special Features:**

One flat 0.936 in.

**Material:**

Titanium

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A121a0