Tube To Hose Straight Adapter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-01-424-5433

Thread Class:2a 1st endMaximum Operating Temp:160.0 degrees fahrenheit single responseEnd Application:Xm56 smoke generatorConnection Style:Gripping nipple (nose) 2nd endConnection Type:Threaded external tube 1st endMaximum Operating Pressure:250.0 pounds per square inch single responseThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endInside Diameter Hose Accommodated:0.750 inches 2nd endOutside Diameter Hose Accommodated:0.750 inches 1st endSous inches 2nd endOutside Diameter Tube Accommodated:0.500 inches 1st endNominallength:3.080 inchesStainless steelThread Series Designator:Unf 1st endSpecification Data:3.043-j516 professional/industrial association standardSheff Life:N/aUnit of Measure:"Panillitarization:NoFig:A080b0	
Maximum Operating Temp:160.0 degrees fahrenheit single responseEnd Application:Xm56 smoke generatorConnection Style:Gripping nipple (nose) 2nd endConnection Type:Threaded external tube 1st endMaximum Operating Pressure:250.0 pounds per square inch single responseThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endInside Diameter Hose Accommodated:0.410 inches 2nd endOutside Diameter Hose Accommodated:0.500 inches 1st endSouside Diameter Tube Accommodated:0.500 inches 1st endNominallength:3.080 inchesMaterial:Stainless steelThread Series Designator:Unf 1st endSpecification Data:81343-j516 professional/industrial association standardSpecification Or Standard:3b figureShelf Life:N/aUnit Of Measure:-Pemilitarization:NoFig:	Thread Class:
160.0 degrees fahrenheit single responseEnd Application:Xm56 smoke generatorConnection Style:Gripping nipple (nose) 2nd endConnection Type:Threaded external tube 1st endMaximum Operating Pressure:250.0 pounds per square inch single responseThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endDiside Diameter Hose Accommodated:0.410 inches 2nd endOutside Diameter Tube Accommodated:0.750 inches 1st endSolon inches 1st endOutside Diameter Tube Accommodated:0.750 inches 2nd endOutside Diameter Tube Accommodated:0.500 inches 1st endNominallength:3.080 inchesMaterial:Stainless steelThread Series Designator:Unf 1st endSpecification Data:81343-j516 professional/industrial association standardShigureShelf Life:N/aUnit Of Measure:Femilitarization:NoFig:	2a 1st end
End Application:Xm56 smoke generatorConnection Style:Gripping nipple (nose) 2nd endConnection Type:Threaded external tube 1st endMaximum Operating Pressure:250.0 pounds per square inch single responseThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endOutside Diameter Hose Accommodated:0.410 inches 2nd endOutside Diameter Hose Accommodated:0.500 inches 1st endSoutide Diameter Tube Accommodated:0.500 inches 1st endNominallength:3.080 inchesStatinless steelThread Series Designator:Unf 1st endSpecification Data:81343-j516 professional/industrial association standardShelf Life:N/aUnit Of Measure:Pemilitarization:NoFig:	Maximum Operating Temp:
Xm56 smoke generatorConnection Style:Gripping nipple (nose) 2nd endConnection Type:Threaded external tube 1st endMaximum Operating Pressure:250.0 pounds per square inch single responseThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endInside Diameter Hose Accommodated:0.410 inches 2nd endOutside Diameter Tube Accommodated:0.500 inches 1st endSoutide Diameter Tube Accommodated:0.500 inches 1st endMominallength:3.080 inchesMaterial:Stainless steelThread Series Designator:Unf 1st endSpecification Data:81343-j516 professional/industrial association standardShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	160.0 degrees fahrenheit single response
Connection Style: Gripping nipple (nose) 2nd end Connection Type: Threaded external tube 1st end Maximum Operating Pressure: 250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Matide Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No	End Application:
Gripping nipple (nose) 2nd end Connection Type: Threaded external tube 1st end Maximum Operating Pressure: 250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Seat Angle: 37.0 degrees 1st end Inside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: 3.080 inches 3.080 i	Xm56 smoke generator
Connection Type: Threaded external tube 1st end Maximum Operating Pressure: 250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Seat Angle: 37.0 degrees 1st end Inside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Hose Accommodated: 0.750 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification O Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No	Connection Style:
Threaded external tube 1st end Maximum Operating Pressure: 250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Seat Angle: 37.0 degrees 1st end Inside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Hose Accommodated: 0.750 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No	Gripping nipple (nose) 2nd end
Maximum Operating Pressure:250.0 pounds per square inch single responseThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endInside Diameter Hose Accommodated:0.410 inches 2nd endOutside Diameter Hose Accommodated:0.750 inches 2nd endOutside Diameter Tube Accommodated:0.500 inches 1st endNominallength:3.080 inchesMaterial:Stainless steelThread Series Designator:Unf 1st endSpecification Data:81343-j516 professional/industrial association standard3b figureShelf Life:N/aUnit Of Measure:Demilitarization:NoFigi:	Connection Type:
250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Hose Accommodated: 0.750 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No	Threaded external tube 1st end
Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Tube Accommodated: 0.750 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No	Maximum Operating Pressure:
0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Hose Accommodated: 0.750 inches 2nd end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.080 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No	250.0 pounds per square inch single response
Seat Angle: 37.0 degrees 1st end Inside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Hose Accommodated: 0.750 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No	Thread Size:
37.0 degrees 1st end Inside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Hose Accommodated: 0.750 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: 3.080 inches 3.080 in	0.750 inches 1st end
Inside Diameter Hose Accommodated: 0.410 inches 2nd end Outside Diameter Hose Accommodated: 0.750 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No	Seat Angle:
0.410 inches 2nd end Outside Diameter Hose Accommodated: 0.750 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No	37.0 degrees 1st end
Outside Diameter Hose Accommodated: 0.750 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inside Diameter Hose Accommodated:
0.750 inches 2nd end Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.410 inches 2nd end
Outside Diameter Tube Accommodated: 0.500 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Outside Diameter Hose Accommodated:
0.500 inches 1st end Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.750 inches 2nd end
Nominallength: 3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Outside Diameter Tube Accommodated:
3.080 inches Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.500 inches 1st end
Material: Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Nominallength:
Stainless steel Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.080 inches
Thread Series Designator: Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Unf 1st end Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Stainless steel
Specification Data: 81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
81343-j516 professional/industrial association standard Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Unf 1st end
Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
Specification Or Standard: 3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	•
3b figure Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3b figure
Unit Of Measure: Demilitarization: No Fiig:	-
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
No Fiig:	Demilitarization:
Fiig:	
-	
-	-