NSN 4730-01-425-4616

Sediment Strainer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-425-4616

view Online at https://acrobasegroup.com/hish/+/30-01-425-4010
Mounting Type:
Unthreaded hole line
Mounting Hole Diameter:
0.620 inches
Mounting Hole Quantity:
4
Body Length:
11.750 inches
Distance Between Mounting Hole Centers:
6.000 inches
End Application:
Strategic sealift conversion ships class., misc. Parts.
Perforation Diameter:
0.062 inches
Perforation Quantity:
144.0 per square inch
Tempurature Rating:
405.0 degrees fahrenheit
Maximum Operating Pressure:
225.0 pounds per square inch
Filtering Media Design:
Perforated single filtering media response
First Intake Connection Type:
Plain face flange line
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
Distance From Bottom Of Body To Center Of Inlet:
9.062 inches
First Intake Flange Outside Diameter:
7.500 inches
First Intake Flange Shape Style:
Round w/unthreaded bolt holes
First Intake Flange Face Style:
Plain
First Intake Flange Thickness:
0.940 inches
Material:
Nickel alloy filtering medium
Material Specification:
Astm b-61 assn standard single material response body
Media For Which Designed:

Water

NSN 4730-01-425-4616

Sediment Strainer - Page 2 of 2



Sty	16	u	=5	ıu	 aı	u	ч.	_

Y strainer w/bolted cover

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000