NSN 4730-01-432-2967

Sediment Strainer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-432-2967

Mounting Type:
Bracket w/drilled hole bottom side
Mounting Hole Diameter:
0.750 inches
Mounting Hole Quantity:
4
Body Length:
16.880 inches
Body Width:
7.500 inches
Body Height:
11.000 inches
Distance Between Mounting Hole Centers:
1.688 inches and 3.062 inches
End Application:
Navy weapon system code jk, wasp class lhd
Tempurature Rating:
Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit
Features Provided:
By-pass valve
Bracket Quantity:
Bracket Quantity: 1
•
1
1 Maximum Operating Pressure:
1 Maximum Operating Pressure: 575.0 pounds per square inch
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design:
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response First Intake Connection Type:
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response First Intake Connection Type: Plain face flange top side
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response First Intake Connection Type: Plain face flange top side First Discharge Connection Relationship To Intake Connection:
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response First Intake Connection Type: Plain face flange top side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response First Intake Connection Type: Plain face flange top side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Discharge Inside Diameter:
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response First Intake Connection Type: Plain face flange top side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Discharge Inside Diameter: 2.000 inches
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response First Intake Connection Type: Plain face flange top side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Discharge Inside Diameter: 2.000 inches First Intake Flange Shape Style:
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response First Intake Connection Type: Plain face flange top side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Discharge Inside Diameter: 2.000 inches First Intake Flange Shape Style: Rectangular w/threaded bolt holes
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response First Intake Connection Type: Plain face flange top side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Discharge Inside Diameter: 2.000 inches First Intake Flange Shape Style: Rectangular w/threaded bolt holes First Discharge Flange Shape Style:
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response First Intake Connection Type: Plain face flange top side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Discharge Inside Diameter: 2.000 inches First Intake Flange Shape Style: Rectangular w/threaded bolt holes First Discharge Flange Shape Style: Rectangular w/threaded bolt holes
Maximum Operating Pressure: 575.0 pounds per square inch Filtering Media Design: Woven single filtering media response First Intake Connection Type: Plain face flange top side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Discharge Inside Diameter: 2.000 inches First Intake Flange Shape Style: Rectangular w/threaded bolt holes First Discharge Flange Shape Style: Rectangular w/threaded bolt holes First Intake Flange Face Style:

Special Features:

145.0 micron rating; 70.0gpm; horizontal design; flanges: sae 4 bolt; intergal bracket

NSN 4730-01-432-2967

Sediment Strainer - Page 2 of 2

Fiig: A24000



Material:
Steel comp 304 filtering medium
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
High pressure angle strainer w/bolted cover
Test Data Document:
53711-0900-lp-003-9000 class 1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment
manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Reference Number Differentiating Characteristics:
As differentiated by navsea 0900-lp-003-9000 class 1
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No