NSN 4730-01-433-1306

Sediment Strainer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4730-01-433-1306 |
|---|
| Mounting Type: |
| Bracket w/threaded hole bottom side |
| Mounting Hole Diameter: |
| 0.500 inches |
| Mounting Hole Quantity: |
| 4 |
| Body Length: |
| 35.000 inches |
| Body Height: |
| 52.250 inches |
| Distance Between Mounting Hole Centers: |
| 10.000 inches |
| End Application: |
| Bob hope class t-akr 300 |
| Mounting Facility Thread Direction: |
| Right-hand |
| Perforation Diameter: |
| 0.250 inches |
| Perforation Quantity: |
| 8.0 per square inch |
| Tempurature Rating: |
| Between 95.0 degrees fahrenheit and 150.0 degrees fahrenheit |
| Bracket Quantity: |
| 1 |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch |
| Filtering Media Design: |
| Perforated single filtering media response |
| First Intake Connection Type: |
| Plain face flange top side |
| Mounting Facility Thread Size: |
| 0.750 inches |
| First Discharge Connection Relationship To Intake Connection: |
| Identical to first intake connection |
| Distance From Bottom Of Body To Center Of Inlet: |
| 24.000 inches |
| First Intake Flange Outside Diameter: |
| 23.500 inches |
| First Intake Flange Shape Style: |
| Round w/unthreaded bolt holes |

Plain

First Intake Flange Face Style:

NSN 4730-01-433-1306

Sediment Strainer - Page 2 of 2



| First Intake Flange Thickness: |
|--|
| 1.438 inches |
| Material: |
| Steel comp 316 filtering medium |
| Material Specification: |
| Astm b61 assn standard single material response body |
| Media For Which Designed: |
| Water |
| Style Designator: |
| Diverted flow plug strainer w/ threader cover |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A24000