NSN 4730-01-444-2675

Sediment Strainer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-444-2675

| Thread | Direction: |
|--------|------------|

Right-hand

Mounting Type:

Inlet connection top side and outlet connection top side

Body Length:

7.125 inches

End Application:

Mars class afs.

Wire Diameter:

0.016 inches

Perforation Diameter:

0.032 inches

Perforation Quantity:

625.0 per square inch

Mesh Size:

20.0

Tempurature Rating:

400.0 degrees fahrenheit

Maximum Operating Pressure:

250.0 pounds per square inch

Filtering Media Design:

Mesh single filtering media response

First Intake Connection Type:

Threaded internal pipe top side

Second Intake Connection Relationship To First Intake Connection:

Identical

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

5.000 inches

First Intake Thread Series Designator:

Npt

First Discharge Thread Series Designator:

Npt

Second Intake Thread Series Designator:

Npt

Second Discharge Thread Series Designator:

Npt

First Intake Thread Size:

2.000 inches

First Discharge Thread Size:

2.000 inches

NSN 4730-01-444-2675 Sediment Strainer - Page 2 of 2



| Second Intake Thread Size: |
|------------------------------------|
| 2.000 inches |
| Second Discharge Thread Size: |
| 2.000 inches |
| First Intake Thread Direction: |
| Right-hand |
| Second Intake Thread Direction: |
| Right-hand |
| Second Discharge Thread Direction: |
| Right-hand |
| First Discharge Thread Direction: |
| Right-hand |
| Material: |
| Stainless steel screening |
| Media For Which Designed: |
| Any acceptable |
| Style Designator: |
| Y strainer w/blow-off plug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A24000