

View Online at <https://aerobasegroup.com/nsn/4730-01-459-3191>

Body Style:

Plain

Concentric Hole Depth:

3.695 inches

Concentric Hole Diameter:

Between 0.242 inches and 0.245 inches

Overall Length:

5.250 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Flared

First End Thread Class:

2a

First End Thread Direction:

Right-hand

Second End Seat Radius:

0.405 inches

End Application:

Used on aircraft carrier cva (n) 65, upper stage sass elevator, sts hatch cover hangar deck

Width Across Flats:

1.625 inches

First End Thread Length:

9.000 inches

Wrenching Feature Style:

Octagon

First Diameter From Wrenching Feature:

0.250 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

3.375 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

4.5625 inches

First Radial Fluid Hole Diameter:

0.375 inches

Distance From First Radial Hole Center To End Of Bolt:

3.695 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

4.625 inches

Wrenching Feature Height:

0.625 inches

First End Thread Series Designator:

Unc

First End Seat Angle:

30.0 degrees

First End Thread Size:

0.875 inches

Special Features:

Item is a spindle for a dog

Material:

Stainless steel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A121a0