

View Online at <https://aerobasegroup.com/nsn/4730-01-460-1559>

**Thread Class:**

2b 2nd end

**Reducer Type:**

Concentric

**End Application:**

Used on palletized loading system (2320013042277)

**Connection Style:**

Shouldered (gasket) (tube) 2nd end

**Connection Type:**

Unthreaded external tube 2nd end

**Thready Qty Per Inch (tpi):**

16 1st end

**Maximum Operating Pressure:**

6000.0 pounds per square inch single response

**Thread Size:**

0.8125 inches 1st end

**Outside Diameter Tube Accommodated:**

1.000 inches 2nd end

**Nominallength:**

1.150 inches

**Product Name:**

Tube end reducer

**Special Features:**

Mrc cqgm is for dynamic (4: 1), static (3: 1) is 9500.0 psi; threads are un/unf; second end thread answers are for the included bl nut; mrc cwfr does not include nut; item is a reducer assembly

**Material:**

Steel comp 12l14

**Material Specification:**

Astm a108 type 12l14 assn standard single material response

**Media For Which Designed:**

Hydraulic fluid 3rd response

**Surface Treatment:**

Zinc and chromate

**Thread Series Designator:**

Un 1st end

**Furnished Items And Quantity:**

1 preformed packing and 1 coupling nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0