

View Online at <https://aerobasegroup.com/nsn/4730-01-460-1559>

Thread Class:

2b 2nd end

Reducer Type:

Concentric

End Application:

Used on palletized loading system (2320013042277)

Connection Style:

Shouldered (gasket) (tube) 2nd end

Connection Type:

Unthreaded external tube 2nd end

Thready Qty Per Inch (tpi):

16 1st end

Maximum Operating Pressure:

6000.0 pounds per square inch single response

Thread Size:

0.8125 inches 1st end

Outside Diameter Tube Accommodated:

1.000 inches 2nd end

Nominallength:

1.150 inches

Product Name:

Tube end reducer

Special Features:

Mrc cqgm is for dynamic (4: 1), static (3: 1) is 9500.0 psi; threads are un/unf; second end thread answers are for the included bl nut; mrc cwfr does not include nut; item is a reducer assembly

Material:

Steel comp 12l14

Material Specification:

Astm a108 type 12l14 assn standard single material response

Media For Which Designed:

Hydraulic fluid 3rd response

Surface Treatment:

Zinc and chromate

Thread Series Designator:

Un 1st end

Furnished Items And Quantity:

1 preformed packing and 1 coupling nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0