NSN 4730-01-464-2013

Sediment Strainer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-464-2013

| Mounting Type: | | | | | | | | |
|---|--|--|--|--|--|--|--|--|
| Unthreaded hole line | | | | | | | | |
| Mounting Hole Quantity: | | | | | | | | |
| 4 | | | | | | | | |
| Body Length: | | | | | | | | |
| 10.000 inches | | | | | | | | |
| Body Width: | | | | | | | | |
| 14.500 inches | | | | | | | | |
| Body Height: | | | | | | | | |
| 15.312 inches | | | | | | | | |
| Perforation Diameter: | | | | | | | | |
| 0.062 inches | | | | | | | | |
| Tempurature Rating: | | | | | | | | |
| 285.0 degrees fahrenheit | | | | | | | | |
| Maximum Operating Pressure: | | | | | | | | |
| 150.0 pounds per square inch | | | | | | | | |
| Filtering Media Design: | | | | | | | | |
| Perforated single filtering media response | | | | | | | | |
| First Intake Connection Type: | | | | | | | | |
| Plain face flange line | | | | | | | | |
| Second Intake Connection Relationship To First Intake Connection: | | | | | | | | |
| Identical | | | | | | | | |
| | | | | | | | | |
| First Discharge Connection Relationship To Intake Connection: | | | | | | | | |
| First Discharge Connection Relationship To Intake Connection: Identical to first intake connection | | | | | | | | |
| | | | | | | | | |
| Identical to first intake connection | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: 10.000 inches | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: 10.000 inches First Intake Flange Outside Diameter: | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: 10.000 inches First Intake Flange Outside Diameter: 2.000 inches | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: 10.000 inches First Intake Flange Outside Diameter: 2.000 inches First Intake Flange Shape Style: | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: 10.000 inches First Intake Flange Outside Diameter: 2.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: 10.000 inches First Intake Flange Outside Diameter: 2.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes First Intake Flange Face Style: | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: 10.000 inches First Intake Flange Outside Diameter: 2.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes First Intake Flange Face Style: Plain | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: 10.000 inches First Intake Flange Outside Diameter: 2.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes First Intake Flange Face Style: Plain Material: | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: 10.000 inches First Intake Flange Outside Diameter: 2.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes First Intake Flange Face Style: Plain Material: Copper alloy body | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: 10.000 inches First Intake Flange Outside Diameter: 2.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes First Intake Flange Face Style: Plain Material: Copper alloy body Media For Which Designed: | | | | | | | | |
| Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 8.188 inches Center To Center Distance Between Connections: 10.000 inches First Intake Flange Outside Diameter: 2.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes First Intake Flange Face Style: Plain Material: Copper alloy body Media For Which Designed: Fuel/oil, hydrocarbon and gas and water | | | | | | | | |

N/a

NSN 4730-01-464-2013

Sediment Strainer - Page 2 of 2



| | • • | | | | | | |
|----|-----|----|----|----|-----|----|----|
| ın | 1+ | Of | ΝЛ | ດລ | CI. | ır | ο. |
| | | | | | | | |

--

Demilitarization:

No

Fiig:

A24000