

View Online at <https://aerobasegroup.com/nsn/4730-01-464-2564>

Mounting Type:

Unthreaded hole bottom side

Mounting Hole Diameter:

22.000 inches

Mounting Hole Quantity:

2

End Application:

Blue ridge class lcc-19

Maximum Operating Pressure:

250.0 pounds per square inch

Filtering Media Design:

Perforated single filtering media response

Product Name:

S&p model no123jt, bolted-cover duplex strainer with jack type plug

Material:

Copper alloy body

Material Specification:

Mil-s-17849 d, ty ii, cl 2 military standard single material response body

Supplementary Features:

8size ips in inches 8.000; face to face p/m 0.125 inches, 26.250 inches; to top 17.000 inches; to bottom 25 inches; diameter of flange in inches 12.375; flange thickness 1.3125 inches; width 43.750 inches; vent connection each cover 0.250 inches; side drain connection, 2, valved 0.750 inches; bottom drain connection, 2, solid 1.500 inches; flange series mil-f-20042c, class 250; service sea water; basket material monel; basket perforation 0.250; basket gross sq inch surface 600.000 inches; ratio: freee are to pipe size 5.0: 1; hydro test pressure 375.0 psi water, ambient; edge support pad to 21.625 inches; mounting bolt distance 43.250 inches; mounting bolt centers 6.500 inches; number and size of mountingbolts 2-0.875; weight in pounds actual dry wgt 1455

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000

Mil-std (military Standard):

Mil-s-17849 spec.