

View Online at <https://aerobasegroup.com/nsn/4730-01-466-2799>

**Maximum Operating Temp:**

275.0 degrees fahrenheit single response

**End Application:**

5420-01-430-5403, carrier, bridge launching

**Maximum Operating Pressure And Media For Which Designed:**

4000.0 pounds per square inch hydraulic fluid, synthetic hydrocarbon base

**Maximum Operating Pressure:**

4000.0 pounds per square inch single response

**Maximum Operating Temperature And Media For Which Designed:**

275.0 degrees fahrenheit hydraulic fluid, synthetic hydrocarbon base

**Product Name:**

Quick disconnect assembly case drain pressure

**Special Features:**

Pressure coupling pressure requirements min burst 10000.0 psig (connected); proof 6000.0 psig; this assembly incorporates a pressure relief valve which will relieve pressure at 100 psig and reseal at 25 psig min; force required to connect coupling halves with no fluid present: 67 lbs

**Material:**

Stainless steel

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-std-171 military standard single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A531s0

**Mil-std (military Standard):**

Mil-std-171 spec.