

View Online at <https://aerobasegroup.com/nsn/4730-01-466-2834>

**Maximum Operating Temp:**

275.0 degrees fahrenheit single response

**End Application:**

5420-01-430-5403, carrier, bridge launching, p/n lscp940001, cagec 19207

**Maximum Operating Pressure And Media For Which Designed:**

800.0 pounds per square inch hydraulic fluid, synthetic hydrocarbon base

**Maximum Operating Pressure:**

800.0 pounds per square inch single response

**Maximum Operating Temperature And Media For Which Designed:**

275.0 degrees fahrenheit hydraulic fluid, synthetic hydrocarbon base

**Product Name:**

Coupling assembly quick disconnect

**Special Features:**

Pressure requirements min burst 1500.0 psig (connected); proof 900.0 psig; this assembly incorporates a pressure bleed valve which is activated when connected to mating half, relieves pressure build up due to volumetric expansion of the fluid

**Material:**

Stainless steel

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-std-171 military standard single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531s0

**Mil-std (military Standard):**

Mil-std-171 spec.