

View Online at <https://aerobasegroup.com/nsn/4730-01-467-1333>

**Overall Length:**

0.950 inches

**Err Default:**

Err default

**Err Default:**

Err default

**Second End Flange Thickness:**

0.950 inches

**Err Default:**

Err default

**Err Default:**

Err default

**Quick Disconnect Method:**

Push-pull all ends

**Maximum Operating Temp:**

175.0 degrees fahrenheit single response

**End Application:**

Cart, support equipmen (se) b-2 bomber aircraft

**Basic Shape Style:**

Rectangular w/ out bolt holes first fluid end connection

**Connection Style:**

Swivel flange, raised first fluid end connection

**Width:**

2.000 inches

**Length:**

2.000 inches

**First End Internal Thread Length:**

0.205 inches

**Second End Internal Thread Length:**

0.205 inches

**Connection Type:**

Flange first fluid end connection

**Second End Relationship With First End:**

Identical

**Maximum Operating Pressure And Media For Which Designed:**

250.0 pounds per square inch air

**Maximum Operating Pressure:**

250.0 pounds per square inch single response

**Maximum Operating Temperature And Media For Which Designed:**

175.0 degrees fahrenheit air

**Thickness:**

0.950 inches

**Raised Face Height:**

0.205 inches

**Raised Face Diameter:**

1.330 inches

**Special Features:**

Quickclamp couples norgren excelon modular components for compressed air system; flanges on components slide into v grooves and sealed with face sealing o'rings; v groove depth is 0.102 inch

**Material:**

Aluminum

**Surface Treatment:**

Paint

**Style Designator:**

Coupling assembly, threaded internal

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531s0