NSN 4730-01-467-1333

Overall Length:

0.950 inches

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-467-1333

0.950 inches
Err Default:
Err default
Err Default:
Err default
Second End Flange Thickness:
0.950 inches
Err Default:
Err default
Err Default:
Err default
Quick Disconnect Method:
Push-pull all ends
Maximum Operating Temp:
175.0 degrees fahrenheit single response
End Application:
Cart, support equipmen (se) b-2 bomber aircraft
Basic Shape Style:
Rectangular w/ out bolt holes first fluid end connection
Connection Style:
Swivel flange, raised first fluid end connection
Width:
2.000 inches
Length:
2.000 inches
First End Internal Thread Length:
0.205 inches
Second End Internal Thread Length:
0.205 inches
Connection Type:
Flange first fluid end connection
Second End Relationship With First End:
Identical
Maximum Operating Pressure And Media For Which Designed:
250.0 pounds per square inch air
Maximum Operating Pressure:
250.0 pounds per square inch single response
Maximum Operating Tempurature And Media For Which Designed:
175.0 degrees fahrenheit air
Thickness:

NSN 4730-01-467-1333

Raised Face Height:

Quick Disconnect Coupling Assembly - Page 2 of 2



0.205 inches
Raised Face Diameter:
1.330 inches
Special Features:
Quickclamp couples norgren excelon modular components for compressed air system; flanges on components slide into v grooves and
sealed with face sealing o'rings; v groove depth is 0.102 inch
Material:
Aluminum
Surface Treatment:
Paint
Style Designator:
Coupling assembly, threaded internal
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A531s0