NSN 4730-01-467-2505

Sediment Strainer - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/4730-01-467-2505
Mounting Type:
nlet connection side and outlet connection side
Body Length:
5.000 inches
End Application:
Strainer; wsd: nimitz class cvn
Perforation Diameter:
0.020 inches
Perforation Quantity:
330.0 per square inch
Maximum Operating Pressure:
375.0 pounds per square inch
Filtering Media Design:
Perforated single filtering media response
First Intake Connection Type:
Socket welding side
First Discharge Connection Relationship To Intake Connection:
dentical to first intake connection
Distance From Bottom Of Body To Center Of Inlet:
2.500 inches
First Intake Inside Diameter:
0.500 inches
First Discharge Inside Diameter:
0.500 inches
Special Features:
Distance from bottom of body to center of inlet, plus required inches for screen removal 4.250; strainers hydrotested to 375 psig for a period
of 60 minutes
Material:
Stainless steel screening
Material Specification:
Qq-n-281, cl a federal specification single material response frame
Media For Which Designed:
Any acceptable
Style Designator:
Y strainer w/threaded cover
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No.

Fiig: A24000

NSN 4730-01-467-2505

Sediment Strainer - Page 2 of 2



Mil-std (military Standard):

Mil-r-83248 spec.