

View Online at <https://aerobasegroup.com/nsn/4730-01-467-8252>

**Second Leg Length:**

1.890 inches

**Quick Disconnect Method:**

Push-pull all ends

**Maximum Operating Temp:**

200.0 degrees fahrenheit single response

**Connection Style:**

Swivel nut, flareless first fluid end connection

**Leg Length:**

1.190 inches

**Connection Type:**

Threaded internal tube first fluid end connection

**Second End Relationship With First End:**

Identical

**Maximum Operating Pressure And Media For Which Designed:**

Err-070

**Maximum Operating Pressure:**

4500.0 pounds per square inch 1st response

**Thread Size:**

0.250 inches first fluid end connection

**Maximum Operating Temperature And Media For Which Designed:**

Err-070

**Outside Diameter Tube Accommodated:**

0.250 inches first fluid end connection

**Special Features:**

Ports plugged with clean metal/plastic plug for shipment or storage. Item use: diesel fuel per vv-f-800 or hydraulic fluid mil-h-5606, 6083, or 46170. Burst pressure rated at 10k psi, temp range -65f to 200f

**Material:**

Steel

**Surface Treatment:**

Zinc and cadmium

**Surface Treatment Specification:**

Qq-z-325 federal specification 1st treatment response or qq-p-416 federal specification 1st treatment response

**Style Designator:**

Coupling assembly

**Supplementary Features:**

For service repair use: a) diesel fuel application, packing ms29513-113.B) hydraulic fluid application: packing ms28775-113

**Thread Series Designator:**

Npsf first fluid end connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A531s0