Quick Disconnect Coupling Half - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-01-469-9187

# **Overall Length:**

2.800 inches

Quick Disconnect Method:

Cam-locking second quick disconnect end

# **End Application:**

Controller, composite repair set, aircraft, p/n daa7257g383-001

## **Connection Style:**

Plain all ends

Connection Type:

Threaded internal pipe first fluid end connection

**Thread Size:** 

1.500 inches all ends

## Product Name:

Sta-lok ii, passive lock coupler x female npt

## **Special Features:**

The coupling shall be supplied with: gasket, cam-lock interface, and pull rings per a-a-59326; od with cam arms extended 7.160, od

3.560, id 1.500, coupler id 2.130 inches; per manufacturer suggested gasket pressure is m 65 to 275 psi

#### Material:

Stainless steel body

## Style Designator:

Male coupling half

## **Thread Series Designator:**

Npt all ends

#### **Specification Data:**

81349-mil-c-27487/canceled government specification and 58536-a-a-59326/5 professional/industrial association specification

#### Specification Or Standard:

55 type and 4 class

## Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A531t0

## Mil-std (military Standard):

Mil-c-27487 spec.