

View Online at <https://aerobasegroup.com/nsn/4730-01-477-7929>

**Exterior Color:**

Red

**Quick Disconnect Size:**

0.250 inches all ends

**Maximum Operating Temp:**

180.0 degrees fahrenheit single response

**End Application:**

Aircraft, stratalifter c-135; kc 135r rvsm

**Leg Length:**

0.500 inches

**Second End Relationship With First End:**

Not identical

**Maximum Operating Pressure And Media For Which Designed:**

Err-070

**Maximum Operating Pressure:**

125.0 pounds per square inch single response

**Maximum Operating Temperature And Media For Which Designed:**

180.0 degrees fahrenheit any acceptable

**Product Name:**

Male assembly self-sealing poppeted positive quick disconnect

**Special Features:**

O-ring, wire, nut; 2 pin polarity, low pressure drop for pitot/static systems; suitable for light and medium pressures for air or fluid systems

**Material:**

Aluminum alloy

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type ii, class 2 military specification single treatment response

**Style Designator:**

Coupling assembly

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531s0

**Mil-std (military Standard):**

Mil-a-8625 spec.