## NSN 4730-01-478-5134

Tube Nipple - Page 1 of 1



4730-01-478-5134

| View Online at https://aerobasegroup.com/nsn/4 |
|--|
| Maximum Operating Temp:                        |
| 212.0 degrees fahrenheit single response       |
| End Application:                               |
| Pwedg for naval surface ships                  |
| Connection Style:                              |
| Plain (pipe) 2nd end                           |
| Connection Type:                               |
| Unthreaded internal tube 1st end               |
| <b>Maximum Operating Pressure:</b>             |
| 200.0 pounds per square inch single response   |
| Thread Size:                                   |
| 0.500 inches 2nd end                           |
| Outside Diameter Tube Accommodated:            |
| 0.500 inches 1st end                           |
| Tubing Wall Thickness For Which Designed:      |
| 0.062 inches 1st end                           |
| Reduced Passage Inside Diameter:               |
| 0.375 inches all ends                          |
| Nominallength:                                 |
| 1.870 inches                                   |
| Material:                                      |
| Plastic polypropylene                          |
| Media For Which Designed:                      |
| Water-oil-gas single response                  |
| Style Designator:                              |
| Center wrenching facility                      |
| Shelf Life:                                    |
| N/a  |
| Unit Of Measure:                               |
|  |
| Demilitarization:                              |

No

Fiig:

A080b0