## NSN 4730-01-485-4608

Pipe To Tube Straight Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-485-4608 **Thread Class:** 2a 1st end **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **End Application:** Hydraulic or air system **Connection Style:** Plain (pipe) 2nd end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 1.000 inches 2nd end Seat Angle: 37.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.750 inches 1st end Nominallength: 2.300 inches **Special Features:** Tube normally connected with sleeve and nut Material: Steel **Material Specification:** Mil-f-18866 military specification single material response Media For Which Designed: Hydraulic fluid 1st response **Surface Treatment:** Zinc **Surface Treatment Specification:** Astm b622 ty2 assn standard single treatment response **Thread Series Designator:** Un 1st end **Specification Data:** 81343-j514 professional/industrial association standard and 96906-ms51500 government standard Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 4730-01-485-4608

Pipe To Tube Straight Adapter - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.