

View Online at <https://aerobasegroup.com/nsn/4730-01-489-1850>

**Body Style:**

Plain

**Concentric Hole Depth:**

1.875 inches

**Concentric Hole Diameter:**

0.125 inches

**Overall Length:**

3.750 inches

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Plain

**First End Thread Class:**

2a

**First End Thread Direction:**

Right-hand

**Second End Connection Type:**

Threaded internal pipe

**Second End Style Designator:**

Plain

**Second End Thread Class:**

3b

**Second End Thread Direction:**

Right-hand

**Cotter Pin Hole Diameter:**

0.156 inches

**End Application:**

Scuttle

**Width Across Flats:**

1.500 inches

**First End Thread Length:**

1.125 inches

**Second End Thread Length:**

0.3125 inches

**Wrenching Feature Style:**

Hexagon

**Distance From Bolt End To Hole Center:**

0.281 inches

**First Diameter From Wrenching Feature:**

0.996 inches

**Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:**

1.094 inches

**Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:**

2.969 inches

**First Radial Fluid Hole Diameter:**

0.125 inches

**Second Radial Fluid Hole Diameter:**

0.156 inches

**Distance From First Radial Hole Center To End Of Bolt:**

2.156 inches

**Distance From Second Radial Hole Center To End Of Bolt:**

1.125 inches

**Length From Bearing Surface Of Wrenching Feature To Bolt End:**

3.250 inches

**Wrenching Feature Height:**

0.500 inches

**First End Thread Series Designator:**

Unjef

**First End Thread Size:**

1.000 inches

**Second End Thread Size:**

0.250 inches

**Second End Thread Series Designator:**

Unf

**Special Features:**

Sheave pin hardened to rockwell 63

**Material:**

Steel

**Material Specification:**

Astm a108, 1018 assn standard single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A121a0