

View Online at <https://aerobasegroup.com/nsn/4730-01-489-1850>

Body Style:

Plain

Concentric Hole Depth:

1.875 inches

Concentric Hole Diameter:

0.125 inches

Overall Length:

3.750 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

2a

First End Thread Direction:

Right-hand

Second End Connection Type:

Threaded internal pipe

Second End Style Designator:

Plain

Second End Thread Class:

3b

Second End Thread Direction:

Right-hand

Cotter Pin Hole Diameter:

0.156 inches

End Application:

Scuttle

Width Across Flats:

1.500 inches

First End Thread Length:

1.125 inches

Second End Thread Length:

0.3125 inches

Wrenching Feature Style:

Hexagon

Distance From Bolt End To Hole Center:

0.281 inches

First Diameter From Wrenching Feature:

0.996 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

1.094 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

2.969 inches

First Radial Fluid Hole Diameter:

0.125 inches

Second Radial Fluid Hole Diameter:

0.156 inches

Distance From First Radial Hole Center To End Of Bolt:

2.156 inches

Distance From Second Radial Hole Center To End Of Bolt:

1.125 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

3.250 inches

Wrenching Feature Height:

0.500 inches

First End Thread Series Designator:

Unjef

First End Thread Size:

1.000 inches

Second End Thread Size:

0.250 inches

Second End Thread Series Designator:

Unf

Special Features:

Sheave pin hardened to rockwell 63

Material:

Steel

Material Specification:

Astm a108, 1018 assn standard single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0