NSN 4730-01-495-0531

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-495-0531

Padu Stula
Body Style:
Plain Concentria Usla Depthy
Concentric Hole Depth:
3.680 inches
Concentric Hole Diameter:
0.213 inches
Overall Length:
3.680 inches
First End Connection Type:
Threaded external tube
First End Style Designator:
First End Thread Class:
2a Final Final Directions
First End Thread Direction:
Right-hand
End Application:
Sheave assembly, moveable, rast system
Width Across Flats:
1.500 inches
First End Thread Length:
0.940 inches
Wrenching Feature Style:
First Diameter From Wrenching Feature:
1.180 inches
Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:
2.530 inches
First Radial Fluid Hole Diameter:
0.120 inches
Distance From First Radial Hole Center To End Of Bolt:
1.590 inches
Length From Bearing Surface Of Wrenching Feature To Bolt End:
3.370 inches
Wrenching Feature Height:
0.310 inches
First End Thready Qty Per Inch (tpi):
12 First End Thread Series Designator
First End Thread Series Designator:
Unf
First End Thread Size:
1.000 inches

NSN 4730-01-495-0531

Fluid Passage Bolt - Page 2 of 2



Material:

Steel comp 303 or steel comp 304

Material Specification:

Astm a582, type 303, cond a federal standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 2 federal specification single treatment response

Shelf Life:

N/a

```
Unit Of Measure:
```

Demilitarization:

No

Fiig:

A121a0