

View Online at <https://aerobasegroup.com/nsn/4730-01-500-0161>

Maximum Operating Temp:

200.0 degrees fahrenheit 2nd response

End Application:

5p ram flat compactor

Connection Style:

Socket (tube) 1st end

Connection Type:

Unthreaded internal tube 1st end

Thready Qty Per Inch (tpi):

27 2nd end

Maximum Operating Pressure:

1000.0 pounds per square inch single response

Thread Size:

0.375 inches 2nd end

Width Across Flats:

0.6875 inches 1st end

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Nominallength:

1.280 inches

Product Name:

Push-in tube fitting; aq68-p male connector

Special Features:

Mrc cqgm is burst pressure of tubing, maximum working pressure varies with tubing used; 1st end of fitting is a quick connect-disconnect type fitting, tubing is pushed into the fitting to connect, to disconnect hold down on insert with two fingers and pull tubing out; comes with buna-n o-ring; similar to nsn 4730-01-486-5884.

Material:

Copper alloy

Media For Which Designed:

Air single response

Thread Series Designator:

Nptf 2nd end

Furnished Items And Quantity:

1 preformed packing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0