

View Online at https://aerobasegroup.com/nsn/4730-01-503-5386

Bolt Hole Quantity:         4 1st end         Maximum Operating Temp:         200.0 degrees fahrenheit single response         Connection Style:         Gripping nipple (nose) 2nd end         Flange Shape:         Round with holes 1st end         Connection Type:         Threaded external hose gripping 2nd end         Maximum Operating Pressure:         350.0 pounds per square inch single response         Outside Diameter:         6.000 inches 1st end         Thickness:         0.440 inches 1st end         Bolt Hole Diameter:         0.750 inches 1st end         Bolt Circle Diameter:         0.750 inches 1st end         Flange Face Design:         Raised straight 1st end         Raised Face Height:         0.015 inches 1st end         Raised Face Diameter:         3.280 inches 1st end         Raised Face Diameter:         3.280 inches 1st end         Inside Diameter Hose Accommodated:         2.380 inches 2nd end         Outside Diameter Hose Accommodated:         2.380 inches 2nd end         Nominallength:         3.890 inches         3.890 inches         Special Features:
Maximum Operating Temp:200.0 degrees fahrenheit single responseConnection Style:Gripping nipple (nose) 2nd endFlange Shape:Round with holes 1st endConnection Type:Threaded external hose gripping 2nd endMaximum Operating Pressure:350.0 pounds per square inch single responseOutside Diameter:6.000 inches 1st endBott Hole Diameter:0.440 inches 1st endBott Hole Diameter:0.750 inches 1st endBott Circle Diameter:4.750 inches 1st endFlange Face Design:Raised straight 1st endRaised Face Height:0.015 inches 1st endRaised Face Diameter:3.280 inches 1st endRaised Face Diameter:3.280 inches 2nd endOutside Diameter Hose Accommodated:2.380 inches 2nd endNominallength:3.890 inchesSpecial Features:Nipple and flange bronze casted
200.0 degrees fahrenheit single response Connection Style: Gripping nipple (nose) 2nd end Flange Shape: Round with holes 1st end Connection Type: Threaded external hose gripping 2nd end Maximum Operating Pressure: 350.0 pounds per square inch single response Outside Diameter: 6.000 inches 1st end Thickness: 0.440 inches 1st end Bolt Hole Diameter: 0.450 inches 1st end Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches
Connection Style: Gripping nipple (nose) 2nd end Flange Shape: Round with holes 1st end Connection Type: Threaded external hose gripping 2nd end Maximum Operating Pressure: 350.0 pounds per square inch single response Outside Diameter: 6.000 inches 1st end Thickness: 0.440 inches 1st end Bolt Hole Diameter: 0.750 inches 1st end Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Height: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
Gripping nipple (nose) 2nd endFlange Shape:Round with holes 1st endConnection Type:Threaded external hose gripping 2nd endMaximum Operating Pressure:350.0 pounds per square inch single responseOutside Diameter:6.000 inches 1st endThickness:0.440 inches 1st endBolt Hole Diameter:0.750 inches 1st endBolt Circle Diameter:4.750 inches 1st endFlange Face Design:Raised straight 1st endRaised Face Height:0.015 inches 1st endRaised Face Height:3.280 inches 1st endRaised Face Jameter:3.280 inches 1st endRaised Face Jameter:3.280 inches 1st endRaised Face Diameter:3.280 inches 1st endRaised Face Jameter:3.280 inches 1st endRaised Face Diameter:3.280 inches 2nd endOutside Diameter Hose Accommodated:2.380 inches 2nd endNominallength:3.890 inchesSupecial Features:Napple and flange bronze casted
Flange Shape:Round with holes 1st endConnection Type:Threaded external hose gripping 2nd endMaximum Operating Pressure:350.0 pounds per square inch single responseOutside Diameter:6.000 inches 1st endThickness:0.440 inches 1st endBolt Hole Diameter:0.750 inches 1st endBolt Circle Diameter:4.750 inches 1st endFlange Face Design:Raised straight 1st endRaised Face Height:0.015 inches 1st endRaised Face Diameter:3.280 inches 1st endRaised Face Diameter:3.280 inches 2nd endOutside Diameter Hose Accommodated:2.380 inches 2nd endNominallength:3.890 inchesSpecial Features:Nipple and flange bronze casted
Round with holes 1st endConnection Type:Threaded external hose gripping 2nd endMaximum Operating Pressure:350.0 pounds per square inch single responseOutside Diameter:6.000 inches 1st endThickness:0.440 inches 1st endBolt Hole Diameter:0.750 inches 1st endBolt Circle Diameter:4.750 inches 1st endFlange Face Design:Raised straight 1st endRaised straight 1st endRaised Face Height:0.015 inches 1st endRaised Face Diameter:3.280 inches 2nd endOutside Diameter Hose Accommodated:2.880 inches 2nd endNominallength:3.890 inchesSpecial Features:Nipple and flange bronze casted
Connection Type: Threaded external hose gripping 2nd end Maximum Operating Pressure: 350.0 pounds per square inch single response Outside Diameter: 6.000 inches 1st end Thickness: 0.440 inches 1st end Bolt Hole Diameter: 0.440 inches 1st end Bolt Circle Diameter: 0.750 inches 1st end Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
Threaded external hose gripping 2nd end Maximum Operating Pressure: 350.0 pounds per square inch single response Outside Diameter: 6.000 inches 1st end Thickness: 0.440 inches 1st end Bolt Hole Diameter: 0.440 inches 1st end Bolt Circle Diameter: 0.750 inches 1st end Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches
Maximum Operating Pressure:350.0 pounds per square inch single responseOutside Diameter:6.000 inches 1st endThickness:0.440 inches 1st endBolt Hole Diameter:0.750 inches 1st endBolt Circle Diameter:4.750 inches 1st endFlange Face Design:Raised straight 1st endRaised Face Height:0.015 inches 1st endRaised Face Diameter:3.280 inches 1st endRaised Face Diameter:3.280 inches 2nd endOutside Diameter Hose Accommodated:2.380 inches 2nd endNominallength:3.890 inchesSpecial Features:Nipple and flange bronze casted
350.0 pounds per square inch single response Outside Diameter: 6.000 inches 1st end Thickness: 0.440 inches 1st end Bolt Hole Diameter: 0.750 inches 1st end Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
Outside Diameter: 6.000 inches 1st end Thickness: 0.440 inches 1st end Bolt Hole Diameter: 0.750 inches 1st end Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
6.000 inches 1st end Thickness: 0.440 inches 1st end Bolt Hole Diameter: 0.750 inches 1st end Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
Thickness: 0.440 inches 1st end Bolt Hole Diameter: 0.750 inches 1st end Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
0.440 inches 1st end Bolt Hole Diameter: 0.750 inches 1st end Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
Bolt Hole Diameter: 0.750 inches 1st end Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
0.750 inches 1st end Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
Bolt Circle Diameter: 4.750 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
<ul> <li>4.750 inches 1st end</li> <li>Flange Face Design:</li> <li>Raised straight 1st end</li> <li>Raised Face Height:</li> <li>0.015 inches 1st end</li> <li>Raised Face Diameter:</li> <li>3.280 inches 1st end</li> <li>Inside Diameter Hose Accommodated:</li> <li>2.380 inches 2nd end</li> <li>Outside Diameter Hose Accommodated:</li> <li>2.880 inches 2nd end</li> <li>Nominallength:</li> <li>3.890 inches</li> <li>Special Features:</li> <li>Nipple and flange bronze casted</li> </ul>
Flange Face Design: Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
Raised straight 1st end Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
Raised Face Height: 0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
0.015 inches 1st end Raised Face Diameter: 3.280 inches 1st end Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
Raised Face Diameter:3.280 inches 1st endInside Diameter Hose Accommodated:2.380 inches 2nd endOutside Diameter Hose Accommodated:2.880 inches 2nd endNominallength:3.890 inchesSpecial Features:Nipple and flange bronze casted
<ul> <li>3.280 inches 1st end</li> <li>Inside Diameter Hose Accommodated:</li> <li>2.380 inches 2nd end</li> <li>Outside Diameter Hose Accommodated:</li> <li>2.880 inches 2nd end</li> <li>Nominallength:</li> <li>3.890 inches</li> <li>Special Features:</li> <li>Nipple and flange bronze casted</li> </ul>
Inside Diameter Hose Accommodated: 2.380 inches 2nd end Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
<ul> <li>2.380 inches 2nd end</li> <li>Outside Diameter Hose Accommodated:</li> <li>2.880 inches 2nd end</li> <li>Nominallength:</li> <li>3.890 inches</li> <li>Special Features:</li> <li>Nipple and flange bronze casted</li> </ul>
Outside Diameter Hose Accommodated: 2.880 inches 2nd end Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
<ul> <li>2.880 inches 2nd end</li> <li>Nominallength:</li> <li>3.890 inches</li> <li>Special Features:</li> <li>Nipple and flange bronze casted</li> </ul>
Nominallength: 3.890 inches Special Features: Nipple and flange bronze casted
3.890 inches Special Features: Nipple and flange bronze casted
Special Features: Nipple and flange bronze casted
Nipple and flange bronze casted
Material:
Nickel alloy flange
Material Specification:
Qq-n-281 federal specification single material response socket
Qq-n-281 federal specification single material response socket Shelf Life:

--



Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-b-24480 spec.