## NSN 4730-01-506-5047

Pipe To Tube Elbow - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-01-506-5047

Thread Class:
2a 1st end
Maximum Operating Temp:
175.0 degrees fahrenheit single response
End Application:
Laundry advanced syste (lads), contractor logistics support(cls) nsn 3510-01-463-0114, contract daak60-97-c-9222 tm 10-3510-221-24pc (lads), contractor logistics support(cls) nsn 3510-01-463-0114, contract daak60-97-c-9222 tm 10-3510-221-24pc (lads), contractor logistics support(cls) nsn 3510-01-463-0114, contract daak60-97-c-9222 tm 10-3510-221-24pc (lads), contractor logistics support(cls) nsn 3510-01-463-0114, contract daak60-97-c-9222 tm 10-3510-221-24pc (lads), contractor logistics support(cls) nsn 3510-01-463-0114, contract daak60-97-c-9222 tm 10-3510-221-24pc (lads), contractor logistics support(cls) nsn 3510-01-463-0114, contract daak60-97-c-9222 tm 10-3510-221-24pc (lads), contract daak60-97-c-9220 tm 10-3510-221-24pc (lads), contract daak60-97-c-97-c-97-c-97-c-97-c-97-c-97-c-97-
Connection Style:
Plain (pipe) 2nd end
Connection Type:
Threaded external tube 1st end
Maximum Operating Pressure:
260.0 pounds per square inch single response
Thread Size:
0.625 inches 1st end
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Pipe Wall Thickness Designation For Which Designed:
Standard 2nd end
Material:
Copper alloy
Thread Series Designator:
Unf 1st end
Furnished Items And Quantity:
1 nut with sleeve
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A080b0