NSN 4730-01-509-2305

Pipe Flange - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4730-01-509-2305

si Thickess: 1.750 incles Center Tocent Distance Between Bolt Holes Along Width: 1.241 incles Center To Center Distance Between Bolt Holes Along Length: 1.241 incles Center To Center Distance Between Bolt Holes Along Length: 1.241 incles Center Distance Between Bolt Holes Along Length: 1.241 incles Distances Bolt Edge To Bolt Hole Center Distance Along Midth: 1.351 incles Distances Bolt Edge To Bolt Hole Center Distance Along Midth: 1.351 incles Distances Bolt Edge To Bolt Hole Center Distance Along Midth: 1.351 incles Bolt Edge To Bolt Hole Center Distance Along Length: 1.350 incles Bolt Edge To Bolt Hole Center Distance Along Length: 1.500 incles Bolt Edge To Bolt Hole Center Distance Along Length: 1.500 incles Bolt Edge To Bolt Hole Center Distance Along Length: 1.500 incles Bolt Edge To Bolt Hole Center: 1.500 incles Bolt Edge To Bolt Hole Center: 1.500 incles Bolt Edge To Bolt Hole Center:	Thread Class:	
1/29 Inches Caper To Center Distance Between Bolt Holes Along Width: 1/28 Inches Caper To Center Distance Between Bolt Holes Along Length: 1/28 Inches Outside Edge To Bolt Hole Center Distance Along Width: 0/136 Inches Outside Edge To Bolt Hole Center Distance Along Length: 0/136 Inches Batter Destrict Distance Along Length: 0/136 Inches Batter Destrict Distance Along Length: 1.500 Inches Batter Destrict Distance Along Length: 1.500 Inches Batter Destrict Destrict Distance Along Length: 1.500 Inches Batter Destrict Destric	3b	
Center O center Distance Between Bolt Holes Along Width: 1.281 indues Center To Center Distance Between Bolt Holes Along Length: 1.281 indues Outside Edge To Bolt Hole Center Distance Along Width: 0.135 indues Bott Hole Countity: 0.135 indues Bott Hole Countity: 1.35 indues Flange Length: 1.50 indues Plange Width: 1.50 indues Bott Hole Diameter: 0.344 indues Plane Kellon Style: Plan face Recuer Flange Hole Type: Concentric Reduer Flange Kontonston: Intered Steles Designator: Unit Receine Starter Condition: Re	Thickness:	
1281 Indes Center Distance Between Bolt Holes Along Length: 1281 Indes Outside Edge To Bolt Hole Center Distance Along Width: Outside Edge To Bolt Hole Center Distance Along Length: Outside Edge To Bolt Hole Center Distance Along Length: Outside Edge To Bolt Hole Center Distance Along Length: Outside Edge To Bolt Hole Center Distance Along Length: Outside Edge To Bolt Hole Center Distance Along Length: Outside Edge To Bolt Hole Center Distance Along Length: Outside Edge To Bolt Hole Center Distance Along Length: Outside Edge To Bolt Hole Center Distance Along Length: Ott Hole Quantity: 5 Bolt Hole Quantity: 5 Insee Length: 1.550 Inches Edde Hole Dianeter: 1.550 Inches Balage Section Style: Plane Section Style: Plan face Recuer Flange Hole Type: Concentric Growen Hoed Series Designator: Unj Receter Style Condition: Receter Selection Style: Outside Condition: Receter Style Districtation: Receter Selectin Style: Outr	1.750 inches	
Center To Center Distance Between Bolt Holes Along Length: 1.281 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.135 inches Det Hole Quantity: 3 Flange Length: 1.550 inchos End Apoltaction: 5 Plage Motht: 1.550 inchos Endage Wotht: 1.550 inchos Bott Hole Baneter: 0.344 inches Plange Section Style: P	Center To Center Distance Between Bolt Holes Along Width:	
1.281 Inches Outside Edge To Bolt Hole Center Distance Along Width: 0.135 Inches Outside Edge To Bolt Hole Center Distance Along Length: 0.135 Inches Bolt Hole Cuantity: 5 Flange Length: 1.550 Inches End Application: 1.550 Inches Plange Width: 1.550 Inches Bolt Hole Diameter: 0.344 Inches Plange Section Style: Plana Face Reducer Flange Hole Type: Concentric Screw Thread Series Designator: Unj Redes Seating Surface Condition: Machined Thready Oxy Per Inch (tpi): 20 Austinkes Chitality Code Justification: Feat Untreceder Reducer Hole Diameter: 1.179 Inches Special Features: Verspress Resential; pressure test fixture, square flange with 4 unthreaded bot holes; 1.179 Inch intel reduced to 4.375 inch	1.281 inches	
Cuside Edge To Bolt Hole Center Distance Along Width:0.135 inchesOutsice Edge To Bolt Hole Center Distance Along Length:0.135 inchesBott Hole Quartity:5Fange Length:1.550 inchesEndaplication:1.550 inchesEndaplication:1.550 inchesBalle Width:1.550 inchesBott Hole Diameter:0.341 inchesPlange Section Style:Plange Section Style:OrecentricConcentricBace Stating Surface Condition:NachinedInteraction Style:20Concentric </td <td>Center To Center Distance Between Bolt Holes Along Length:</td>	Center To Center Distance Between Bolt Holes Along Length:	
0.135 inchesOutside Edge To Bolt Hole Center Distance Along Length:0.135 inchesBolt Hole Center Distance Along Length:10.100 Colspan="2">10.100 Colspan="2">10.100 Colspan="2"Brage Length:1.550 inchesEdd polication:10.100 Colspan="2"10.100 Colspan="2" <td cols<="" td=""><td>1.281 inches</td></td>	<td>1.281 inches</td>	1.281 inches
Cuside Edge To Bolt Hole Center Distance Along Length:0.135 inchesBolt Hole Quantity:7Flange Length:1.550 inchesEnd Application:NipFlange Width:1.550 inchesBolt Hole Diameter:0.344 inchesFlange Section Style:Plana GodReduer Flange Hole Type:ConcentricBort Hole Selignator:UnjStread Condition:AuchinedConcentricSection Style:1.50AustinkeFlane Section Style:Out Hole Nettio:AustinkeFlane Selignator:UnjStread Condition:AustinkeChrose Stread Condition:AustinkeChrose Stread Condition:AustinkeChrose Stread Condition:Flane Section Stread Condition:Flane Section Stread Condition:Flana Section Se	Outside Edge To Bolt Hole Center Distance Along Width:	
0.135 inches Bot Hole Quantity: 5 Flange Length: 1.550 inches End Application: Ship Flange Width: 1.550 inches Bott Hole Diameter: 0.344 inches Flange Section Style: Plain face Reducer Flange Hole Type: Concentric Reducer Flange Hole Type: Concentric Hone Satise Default Stress Designator: Unj Flaneed Stress Designator: Unj Reducer Flange Hole (tpi): 20 Thread Stress Designator: Unj Refault Stresse Designator: Unit Stresse Stresse Designator: Unit Stresse Stresse Designator: Unit Stresse Stresse Designator: Unit Stresse Stresse Designator: Stresse Stresse Designator: Stresse Stresse Designator: Unit Stresse Stresse Designator: Stresse Stresse Designator:	0.135 inches	
Bot Hole Quantity: 5 Finage Length: 1.550 inches End polication: Ship Flange With: 1.550 inches Bott Hole Diameter: 0.344 inches Flange Section Style: Plange Mole Type: Concentic Reducer Flange Hole Type: Concentic Prived Streise Designator: Unj Flanes Quard Condition: National Streise Designator: Oxignation Gate Streise Designator: Unj Flanes Quard Condition: National Streise Streise Designator: Oxignation Concentic Streise Streise Designator: Unit Flanese Condition: Streise Streise Designation: Oxignation Concentic Thread Streise Concentic Thread Streise Concentic Concentic Concentic Concentic Concentic	Outside Edge To Bolt Hole Center Distance Along Length:	
5 Flange Length: 1.550 inches End Application: Ship Flange Width: 1.550 inches Bolt Hole Diameter: 0.344 inches Flange Section Style: Plain face Reducer Flange Hole Type: Concentric Screw Thread Series Designator: Unj Face Seating Surface Condition: Achined Thready Cly Per Inch (tpi): 20 Thread Size: 0.4375 inches Flaned Thread Reducer Hole Diameter: 1.179 inches Verage Hole Type: Concert for Machined Thready Cly Per Inch (tpi): 20 Thread Size: 0.4375 inches Cinclity Code Justification: Feat Horeded Reducer Hole Diameter: 1.179 inches Special Features: Verspon system essential; pressure test fixture, square flange with 4 unthreaded but blocks; 1.179 inch inlet reduced to 4.375 inche	0.135 inches	
Farage Length: 1.550 inches Farage Width: 1.550 inches Farage Width: 1.550 inches Bolte Dameter: 0.344 inches Flange Section Style: Plain face Raducer Flange Hole Type: Concentric Concentric Machined Thread Series Designator: Unj Fare Section Style: Actioned Thready Oxy Per Inch (tpi): 20 Thread Stries 0.4375 inches Christing Condition: 1.4375 inches Christing Conduction: 1.4375 inches Christing Conduction: 1.4375 inches Christing Conduction: Face Variation: 1.719 inches Kerter Variation: Variation: Variation: Variation: Variation: Variation: Variation: Variation: Variation: Varia	Bolt Hole Quantity:	
1.550 inches Finge Width: 1.550 inches Bolt Hole Diameter: 0.344 inches Flange Section Style: Plain face Reducer Flange Hole Type: Concentric Concentric Unj Flaned Series Designator: Unj Flaned Series Designator: 20 Flaned Stripe Hole Type: Concentric Machined Thready Day Per Inch (tpl): 20 Flaned Stripe 1.179 inches Flaned Stripe 1.179 inches Flaned Stripe Vertreader Reducer Hole Diameter: 1.179 inches Special Features: Vapon system essential; pressure test future, square flange with 4 unthreaded bot holes; 1.179 inch inter tenden de. 4.375 inche	5	
End Application: Ship Flange Width: 1.550 inches Bott Hole Diameter: 0.344 inches Flange Section Style: Plain face Reducer Flange Hole Type: Concentric Concentric Brease Section Surface Condition: Notice Machined Threads Surface Condition: 20 Thread Surface Condition: 0.4375 inches Caticality Code Justification: Fate Intreaded Reducer Hole Diameter: 1.179 inches Special Features: Veapon system essentiat; pressure test future, square flange with 4 unthreaded bot holes; 1.179 inches intereduced to 4.375 inches	Flange Length:	
ShipFange Width:1.550 inchesSolt Hole Diameter:0.344 inchesFange Section Style:Fange Section Style:Plain faceReducer Flange Hole Type:ConcentricBorew Thread Series Designator:UnjFace Seating Surface Condition:MachinedThready Ope Inch (pi):20Chread Size:0.4375 inchesFateIntreaded Reducer Hole Diameter:1.179 inchesSpecial Factures:1.179 inchesKeapon system essential; pressure test fixture, square flange with 4 unthreaded bot holes; 1.179 inch inter terduced to 4.3475 inchesKeapon system essential; pressure test fixture, square flange with 4 unthreaded bot holes; 1.179 inch inter terduced to 4.3475 inchesKeapon system essential; pressure test fixture, square flange with 4 unthreaded bot holes; 1.179 inch inter terduced to 4.3475 inchesKeapon system essential; pressure test fixture, square flange with 4 unthreaded bot holes; 1.179 inch inter terduced to 4.3475 inchesKeapon system essential; pressure test fixture, square flange with 4 unthreaded bot holes; 1.179 inch inter terduced to 4.3475 inches	1.550 inches	
Flage Width:1.550 inches504 Hole Diameter:0.344 inchesFlage Section Style:Plain faceReducer Flange Hole Type:ConcentricScrew Thread Series Designator:UnjFace Seating Surface Condition:MachinedThready Qhy Per Inch (tpi):20Chread Size:0.4375 inchesFateHurtander Condition:1.719 inchesPateWater State Seating Surface Condition:1.719 inchesPateHurtander State Seating State Seating State Seating State Seating Se	End Application:	
1.50 Inches Bolt Hole Diameter: 0.344 inches Flange Section Style: Plain face Reducer Flange Hole Type: Concentric Screw Thread Series Designator: Unj Face Seating Surface Condition: Machined Thready Qty Per Inch (tpi): 20 Thread Size: 0.4375 inches Chiticality Code Justification: Face 1.179 inches Special Features: Variander Size: 1.179 inches Special Features: Wapon system essential; pressure test fixture, square flange with 4 unthreaded bot holes; 1.179 inch init reduced to 4.3475 inches	Ship	
Bott Hole Diameter:0.344 inchesFlange Section Style:Plain faceReducer Flange Hole Type:ConcentricSorew Thread Series Designator:UnjFace Seating Surface Condition:MachinedThready Qty Per Inch (tpi):20Thread Size:0.4375 inchesChritealty Code Justification:Face1.716 inchesParender Hole Diameter:1.719 inchesSpecial Features:Veapon system essentiat; pressure test fixture, square flange with 4 unthreaded bot holes; 1.179 inch initer educed to 4.375 inchesHoragen duetter1.720 inchesSpecial Features:Veapon system essentiat; pressure test fixture, square flange with 4 unthreaded bot holes; 1.179 inch initer educed to 4.375 inchesHoragen duetterVeapon system essentiat; pressure test fixture, square flange with 4 unthreaded bot holes; 1.179 inch initer educed to 4.375 inchesHoragen duetterHoragen due	Flange Width:	
0.344 inches Flange Section Style: Plain face Reducer Flange Hole Type: Concentric Screw Thread Series Designator: Unj Face Seating Surface Condition: Machined Thready Qty Per Inch (tpi): 20 Thread Size: 0.4375 inches Criticality Code Justification: Feat Unthreaded Reducer Hole Diameter: 1.179 inches Special Features: Veapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch	1.550 inches	
Flange Section Style:Plain faceReducer Flange Hole Type:ConcentricConcentricScrew Thread Series Designator:UnjFace Seating Surface Condition:MachinedThready Qty Per Inch (tpi):20Chread Size:0.4375 inchesFatePretaced Reducer Hole Diameter:1.179 inchesSpecial Features:NationsSpecial Features:Veapon system essential; pressure test fixture, square flange with 4 unthreaded bot holes; 1.179 inchiniet reduced to 4.3475 inchiniet reduced to 4.3455 inchiniet re	Bolt Hole Diameter:	
Plain face Reducer Flange Hole Type: Concentric Screw Thread Series Designator: Unj Face Seating Surface Condition: Machined Thready Qty Per Inch (tpi): 20 Thread Size: 0.4375 inches Fact Virthreaded Reducer Hole Diameter: 1.179 inches Special Features: Vieapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inter teduced to 4.375 inches	0.344 inches	
Reducer Flange Hole Type:ConcentricConcentricCorcer Thread Series Designator:UnjFace Seating Surface Condition:MachinedThready Qty Per Inch (tpi):20Thread Size:0.4375 inchesCriticality Code Justification:FeatUntreaded Reducer Hole Diameter:1.179 inchesSpecial Features:Veapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inche interdeuced to .4375 inchKieaded outlet	Flange Section Style:	
Concentric Screw Thread Series Designator: Unj Face Seating Surface Condition: Machined Thready Qty Per Inch (tpi): 20 Thread Size: 0.4375 inches Criticality Code Justification: Feat Chthreaded Reducer Hole Diameter: 1.179 inches Special Features: Veapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch	Plain face	
Screw Thread Series Designator:UnjFace Seating Surface Condition:MachinedThready Qty Per Inch (tpi):20Thread Size:0.4375 inchesCriticality Code Justification:FeatDthreaded Reducer Hole Diameter:1.179 inchesSpecial Features:Wapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inche interdeuted to .4375 inch	Reducer Flange Hole Type:	
Unj Face Seating Surface Condition: Machined Thready Qty Per Inch (tpi): 20 Thread Size: 0.4375 inches Criticality Code Justification: Feat Criticality Code Justification: Feat Unthreaded Reducer Hole Diameter: 1.179 inches Special Features: Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch threaded outlet	Concentric	
Face Seating Surface Condition:MachinedMachinedThready Oty Per Inch (tpi):20Dotation:0.4375 inchesCriticality Code Justification:FeatUnthreaded Reducer Hole Diameter:1.179 inchesSpecial Features:Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inche inter duct do .4375 inchHeraded outlet	Screw Thread Series Designator:	
MachinedThready Qty Per Inch (tpi):20Thread Size:0.4375 inchesCriticality Code Justification:FeatDuthreaded Reducer Hole Diameter:1.179 inchesSpecial Features:Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inche inlet reduced to .4375 inche	Unj	
Thready Qty Per Inch (tpi):20Thread Size:0.4375 inchesCriticality Code Justification:FeatUnthreaded Reducer Hole Diameter:1.179 inchesSpecial Features:Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inchthreaded outlet	Face Seating Surface Condition:	
20 Thread Size: 0.4375 inches Criticality Code Justification: Feat Unthreaded Reducer Hole Diameter: 1.179 inches Special Features: Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch threaded outlet	Machined	
Thread Size:0.4375 inchesCriticality Code Justification:FeatUnthreaded Reducer Hole Diameter:1.179 inchesSpecial Features:Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inchthreaded outlet	Thready Qty Per Inch (tpi):	
0.4375 inches Criticality Code Justification: Feat Unthreaded Reducer Hole Diameter: 1.179 inches Special Features: Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch threaded outlet	20	
Criticality Code Justification: Feat Unthreaded Reducer Hole Diameter: 1.179 inches Special Features: Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch threaded outlet	Thread Size:	
Feat Unthreaded Reducer Hole Diameter: 1.179 inches Special Features: Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch threaded outlet	0.4375 inches	
Unthreaded Reducer Hole Diameter: 1.179 inches Special Features: Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch threaded outlet	Criticality Code Justification:	
1.179 inches Special Features: Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch threaded outlet	Feat	
Special Features: Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch threaded outlet	Unthreaded Reducer Hole Diameter:	
Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch threaded outlet	1.179 inches	
threaded outlet	Special Features:	
	Weapon system essential; pressure test fixture, square flange with 4 unthreaded bolt holes; 1.179 inch inlet reduced to .4375 inch	
Material:	threaded outlet	
	Material:	

Stainless steel

NSN 4730-01-509-2305

Pipe Flange - Page 2 of 2



Material Specification:

Astm a276 316l cond a assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 ty vi or vii federal specification single treatment response

Style Designator:

Rectangular, with bolt holes

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A23300