NSN 4730-01-510-3685

Sediment Strainer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-510-3685

Mounting Type:
Inlet connection top
Body Diameter:
0.810 inches
Body Inside Diameter:
0.560 inches
Mounting Flange Thickness:
0.380 inches
Mounting Flange Bolt Hole Quantity:
1
Mounting Flange Bolt Hole Diameter:
1.310 inches
Mounting Flange Bolt Circle Diameter:
1.410 inches
End Application:
Ship; misc parts hy
Wire Diameter:
0.0021 inches
Mesh Size:
200.0
Mounting Flange Diameter:
1.528 inches
Tempurature Rating:
160.0 degrees fahrenheit
Bodylength:
3.250 inches
Maximum Operating Pressure:
10.0 pounds per square inch
Criticality Code Justification:
Feat
Filtering Media Design:
Mesh single filtering media response
First Intake Connection Type:
Socket welding top
First Discharge Connection Relationship To Intake Connection:
Not identical
First Discharge Connection Type:
Unthreaded external tube bottom
First Discharge Outside Diameter:
0.810 inches
First Intake Inside Diameter:
0.560 inches

NSN 4730-01-510-3685

Sediment Strainer - Page 2 of 2

Product Name:



Strainer
Special Features:
Weapon system essential; body has 36 .25 inch perferations; mesh liner is .56 inch diameter and 2.750 inch long; has .125 inch diameter
wire handle, nichol copper
Material:
Stainless steel body
Material Specification:
Rr-w-360, type 1, cl 1 federal specification single material response screening
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Cylindrical w/ container (rigid) and mounting flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000