NSN 4730-01-510-3685

Sediment Strainer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-510-3685

Mounting Type: Inlet connection top **Body Diameter:** 0.810 inches **Body Inside Diameter:** 0.560 inches **Mounting Flange Thickness:** 0.380 inches **Mounting Flange Bolt Hole Quantity:** 1 Mounting Flange Bolt Hole Diameter: 1.310 inches Mounting Flange Bolt Circle Diameter: 1.410 inches **End Application:** Ship; misc parts hy Wire Diameter: 0.0021 inches Mesh Size: 200.0 **Mounting Flange Diameter:** 1.528 inches **Tempurature Rating:** 160.0 degrees fahrenheit **Bodylength:**

3.250 inches

Maximum Operating Pressure:

10.0 pounds per square inch

Criticality Code Justification:

Feat

Filtering Media Design:

Mesh single filtering media response

First Intake Connection Type:

Socket welding top

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Unthreaded external tube bottom

First Discharge Outside Diameter:

0.810 inches

First Intake Inside Diameter:

0.560 inches

NSN 4730-01-510-3685

Sediment Strainer - Page 2 of 2



Product Name:

Strainer

Special Features:

Weapon system essential; body has 36.25 inch perferations; mesh liner is .56 inch diameter and 2.750 inch long; has .125 inch diameter wire handle, nichol copper

Material:

Stainless steel body

Material Specification:

Rr-w-360, type 1, cl 1 federal specification single material response screening

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

Cylindrical w/ container (rigid) and mounting flange

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A24000