
# NSN 4730-01-512-0583

Sediment Strainer - Page 1 of 2



## Mounting Type:

Unthreaded hole side

## **Mounting Hole Quantity:**

4

## Body Length:

6.190 inches

#### **Body Height:**

7.750 inches

#### **End Application:**

Strainer simplex 1 inch 150flge 1/16p-30 mesh

#### Mesh Size:

30.0

#### **Tempurature Rating:**

425.0 degrees fahrenheit

#### **Features Provided:**

Drain plug

## **Maximum Operating Pressure:**

150.0 pounds per square inch

## Filtering Media Design:

Perforated single filtering media response

## First Intake Connection Type:

Plain face flange side

## Second Intake Connection Relationship To First Intake Connection:

Identical

## Second Intake Connection Type:

Plain face flange side

## First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

## Distance From Bottom Of Body To Center Of Inlet:

4.630 inches

#### First Intake Flange Shape Style:

Round w/unthreaded bolt holes

## First Discharge Flange Shape Style:

Round w/unthreaded bolt holes

## First Intake Flange Face Style:

Plain

## First Discharge Flange Face Style:

Plain

#### **Product Name:**

1 " is-15-f-150 bronze 3/16p

#### **Special Features:**

Item includes: 1 body, 1 cover, 1 locking bar, 1 locking handle, 1 cover gasket, 1 cleanout plug, 1 air vent, 1 locking handle stud, 1 pivot stud, 1 pivot stud nut, and 1 perforated basket with mesh liner; clearance from bottom of body required is 11.750 in



# NSN 4730-01-512-0583

Sediment Strainer - Page 2 of 2



Material:

Copper alloy 836 body

**Material Specification:** 

Astm b62 c83600 assn standard all material responses body

Media For Which Designed:

Fuel/oil, hydrocarbon and gas and water

Style Designator:

Diverted flow basket strainer w/bolted cover

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A24000