

View Online at <https://aerobasegroup.com/nsn/4730-01-512-0583>

**Mounting Type:**

Unthreaded hole side

**Mounting Hole Quantity:**

4

**Body Length:**

6.190 inches

**Body Height:**

7.750 inches

**End Application:**

Strainer simplex 1 inch 150flge 1/16p-30 mesh

**Mesh Size:**

30.0

**Tempurature Rating:**

425.0 degrees fahrenheit

**Features Provided:**

Drain plug

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Filtering Media Design:**

Perforated single filtering media response

**First Intake Connection Type:**

Plain face flange side

**Second Intake Connection Relationship To First Intake Connection:**

Identical

**Second Intake Connection Type:**

Plain face flange side

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**Distance From Bottom Of Body To Center Of Inlet:**

4.630 inches

**First Intake Flange Shape Style:**

Round w/unthreaded bolt holes

**First Discharge Flange Shape Style:**

Round w/unthreaded bolt holes

**First Intake Flange Face Style:**

Plain

**First Discharge Flange Face Style:**

Plain

**Product Name:**

1 " is-15-f-150 bronze 3/16p

**Special Features:**

Item includes: 1 body, 1 cover, 1 locking bar, 1 locking handle, 1 cover gasket, 1 cleanout plug, 1 air vent, 1 locking handle stud, 1 pivot stud, 1 pivot stud nut, and 1 perforated basket with mesh liner; clearance from bottom of body required is 11.750 in

**Material:**

Copper alloy 836 body

**Material Specification:**

Astm b62 c83600 assn standard all material responses body

**Media For Which Designed:**

Fuel/oil, hydrocarbon and gas and water

**Style Designator:**

Diverted flow basket strainer w/bolted cover

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A24000