NSN 4730-01-519-3966

Tube Fitting Clinch Sleeve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-519-3966

| Casehardening Indicator: |
|---|
| Casehardened |
| Overall Length: |
| 0.363 inches |
| Metallic Hardness Rating: |
| 41.8 rockwell c |
| End Application: |
| Apl update |
| Flange Outside Diameter: |
| 0.367 inches |
| Seat Angle In Deg: |
| 40.0 |
| Sleeve Outside Diameter: |
| 0.312 inches |
| Hose/tube Outside Diameter For Which Designed: |
| 0.250 inches |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| Weapon system essential; requires special cleaning and packaging for oxygen/nitrogen service |
| Material: |
| Steel, ams 5643 |
| Material: |
| Steel comp 630 |
| Surface Treatment: |
| Passivate |
| Style Designator: |
| Flareless |
| Surface Treatment: |
| Passivated, qq-p-35, type 2 |
| Specification Data: |
| 96906-ms51825 government standard and 81343-j514 professional/industrial association standard |
| Specification Or Standard: |
| 28 figure |
| Reference Number Differentiating Characteristics: |
| Cleaning, packaging, and marking iaw mil-std-1330d |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Na. |

No

NSN 4730-01-519-3966

Tube Fitting Clinch Sleeve - Page 2 of 2



Fiig:

T385-j