NSN 4730-01-527-6612

Tube Coupling - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-01-527-6612

| Maximum Operating Temp: |
|--|
| 212.0 degrees fahrenheit single response |
| End Application: |
| Process panel |
| Connection Style: |
| Socket (tube) all ends |
| Connection Type: |
| Unthreaded internal tube all ends |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Outside Diameter Tube Accommodated: |
| 0.500 inches all ends |
| Tubing Wall Thickness For Which Designed: |
| 0.062 inches all ends |
| Nominallength: |
| 2.750 inches |
| Product Name: |
| Union bulkhead |
| Special Features: |
| Black, stainless grap ring; nitrile o'ring; lock nuts up to .5 inch bulkhead thickness |
| Material: |
| Plastic polypropylene |
| Media For Which Designed: |
| Water-oil-gas single response |
| Style Designator: |
| Swivel, wrenching facilities each end |
| Furnished Items And Quantity: |
| 2 lock ring and 2 locknut and 2 nut with sleeve and 2 preformed packing |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| 40001.0 |
| A080b0 |