

View Online at <https://aerobasegroup.com/nsn/4730-01-528-9277>

Thread Class:

2a 2nd end

Maximum Operating Temp:

250.0 degrees fahrenheit single response

End Application:

HIMA-RS-,RS-V,MK

Connection Style:

Flared (tube) 2nd end

Leg Length:

32.0 millimeters 2nd end

Connection Type:

Threaded external tube 2nd end

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Thread Size:

0.750 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Flow Angle:

90.0 degrees

Outside Diameter Tube Accommodated:

0.500 inches 2nd end

Product Name:

Swivel nut elbow

Special Features:

Nha is cylinder tube group, p/n 499-4701; hex across the flats is 0.875 inch

Material:

Steel

Material Specification:

Sae-ams-std-66, 1 dec 98.Sae-ams-std-66, 1 dec 98active assn standard single material response

Media For Which Designed:

Hydraulic fluid 2nd response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-f-18866h, 6 may 87.Mil-f-18866h, 6 may 87inactive military specification single treatment response and sae-ams-c-81562, 1 aug 98.Sae-ams-c-81562, 1 aug 98active assn standard single treatment response

Thread Series Designator:

Unf 2nd end

Furnished Items And Quantity:

1 swivel nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-f-18866h spec.