

View Online at <https://aerobasegroup.com/nsn/4730-01-534-6188>

Mounting Type:

Inlet connection side and outlet connection side

Body Length:

10.500 inches

Body Height:

18.500 inches

End Application:

Ship, lube oil

Perforation Diameter:

0.094 inches

Perforation Quantity:

52.0 per square inch

Features Provided:

Drain plug

Maximum Operating Pressure:

100.0 pounds per square inch

Filtering Media Design:

Perforated single filtering media response

First Intake Connection Type:

Plain face flange side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

12.500 inches

Center To Center Distance Between Connections:

10.500 inches

First Intake Flange Outside Diameter:

7.000 inches

First Intake Flange Shape Style:

Round w/unthreaded bolt holes

First Intake Flange Face Style:

Plain

First Intake Flange Thickness:

0.750 inches

Product Name:

S&p simplexstrainer mod 1450 174yf 2.5 inch

Special Features:

Used for lube oil; has .375 npt drain plug, basket element with handle, yoke cover

Material:

Steel comp 304 screening

Material Specification:

Astm a240 type 304 national specification single material response screening

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

Diverted flow basket strainer w/clamped cover

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000