# NSN 4730-01-534-8661

Quick Disconnect Coupling Half - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-534-8661

# **Pipe Size Accommodated:**

2.000 inches first fluid end connection

#### **Overall Length:**

2.940 inches

#### **Quick Disconnect Method:**

Push-pull first quick disconnect end

#### **Quick Disconnect Size:**

2.000 inches first quick disconnect end

#### **Mating End Identification:**

Snap-tite vhc32-32f or 9400 series

#### **Maximum Operating Temp:**

160.0 degrees fahrenheit single response

#### Depth:

1.320 inches

#### **End Application:**

Jet engine fuel system

#### **Connection Style:**

Push (external) first quick disconnect end

# Leg Length:

1.400 inches

# **Connection Type:**

Threaded internal pipe first fluid end connection

# **Features Provided:**

Self-sealing

# Thready Qty Per Inch (tpi):

11.5 first fluid end connection

# **Maximum Operating Pressure:**

4000.0 pounds per square inch single response

# Thread Size:

2.000 inches first fluid end connection

#### **Product Name:**

Coupler

# **Special Features:**

O'ring, military variation of buna n for hydrocarbon fuels; 316 stainless steel; includes selfsealing valve

#### Material:

Stainless steel

# Media For Which Designed:

Fuel/oil, hydrocarbon single response

# **Style Designator:**

Female coupling half

# **Thread Series Designator:**

Npt first fluid end connection

# NSN 4730-01-534-8661

Quick Disconnect Coupling Half - Page 2 of 2



| She | lf I | Life: |
|-----|------|-------|
|     |      |       |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A531t0